



DG 985 90cm Glass Wing Decorative Hood with ECOPOWER motor



LED



Stop Delay
Timer

DESCRIPTION

90cm Glass Wing Decorative Hood with ECOPOWER motor

LIFE STYLE

Total

COLOURS

REFERENCE

REF. 40485382
EAN. 8421152130421

FEATURES

Ultraslim glass wing decorative hood
Eco power
Backlit electronic panel with white display
Conventional aspiration
3 speeds + 1 intensive
Exhaust capacities:
Free Outlet (m³/h): 895
Max. (m³/h): 807
Min. (m³/h): 315
Noise (LwA) Max Speed 68 dB
Noise (LwA) Min Speed 56 dB
LED illumination
1 stainless steel-aluminium filter
Stop delay timer
Reinforced glass upper structure

DIMENSIONS

Product height (mm): 667-997

Product width (mm): 900

Product depth (mm): 500

Product length (mm):

Net weight (Kg): 13,2

TECH SPECS

PARTICULAR CHARACTERISITICS

Type of hood: Glass Wing

Style: Decoratives

Certificates: CE; CB; Rohs

Ø Outlet (mm): 150

Type of inner light: LED

Inside light Consumption (W): 3

Plug type: European plug

Power rate (V): 220240

Frequency (Hz): 50

Total hood power (W): 286

Number of motors: 1

Motor power (W): 280

Exhaust Capacity - Free Outlet (m3/h): 895

**EU REGULATION NO. 65/2014
&66/2104**

Annual energy consumption AEC kWh/annum (kWh): 56,7

Energy Efficiency Class: A

Fluid Dynamic Efficiency (FDEhood): 30,5

Fluid Dynamic Efficiency class: A

Light Efficiency (Lehood) lux/Watt: 65,2

Lighting Efficiency class: A

Grease Filtering Efficiency class: C

Air flow (Qmin) m3/h: 315

Air flow (Qmax): 631

Air flow (Qboost): 807

Noise (LwA) Min Speed (dB): 56

Noise (LwA) Max Speed (dB): 68

Noise (LwA) boost speed (dB): 72

Off mode Power (Po) W: 0,00

Standby Power (Ps) W: 0,56

Energy Efficiency Index (EEI): 53,3

Time increase factor: 0,9

Electric power input at best efficiency point (Wbep) W:
159,4

Nominal power of the lighting system (WL) W: 6

**Average illumination of the lighting system on the cooking
surface (Emiddle) Lux:** 391

ACCESSORIES

Anti Return valve: Yes

Outlet reduction: Yes

Optional Charcoal Filter: D4C

Charcoal filter description: CHARCOAL FILTER D4C

Conventional recirculation kit (with tube cover): 40490147

MODELS

Number of filters: 1

Filter description: Stainless Steel filters

Control panel: Backlit electronic control with white display

Stop delay timer: Yes

Filter saturation indicator: Yes

Number of speeds: 3+1

PRODUCT INFORMATION SHEET - DELEGATED REGULATION (EU) 65/2014

Supplier name or trademark: TEKA

Model identifier: DG 985

Annual Energy Consumption: 56,7

Energy Efficiency Class: A

Fluid Dynamic Efficiency: 30,5

Fluid Dynamic Efficiency class: A

Lighting Efficiency: 65,2

Lighting Efficiency class: A

Grease Filtering Efficiency class: C

Air flow (min speed normal use): 315

Air flow (max speed normal use): 631

Air flow (intensive or boost use): 807

**Airborne acoustical A-weighted sound power emissions
(min speed normal use):** 56

**Airborne acoustical A-weighted sound power emissions
(max speed normal use):** 68

**Airborne acoustical A-weighted sound power emissions
(intensive or boost use):** 72

Power consumption in off mode (W): 0,00

Power consumption in standby mode (W): 0,56



DG 985

ENERGY LABEL

